



EXTRUTECH PLASTICS, INC.

"Custom Extruder of Close Tolerance Profiles"

FOR QUOTE, FAX TO (920) 684-4344

Pre-Hung Corrosion Proof PVC Interior Doors

Note: Painting or use as Exterior Door will void Door Warranty.

1. Door Location

- Door will be for Interior use only.

2. Door Swing

Circle your choice

LEFT HAND	RIGHT HAND	LEFT HAND	RIGHT HAND
Quantity _____	Quantity _____	Quantity _____	Quantity _____
SWING- OUT (Door Swing)		SWING- IN (Door Swing)	

View Door Unit from outside room.

5. Standard Door Size

Size out to out Rough opening

- 2868 34" x 82" 35"x 83"
- 3068 38" x 82" 39"x 83"
- 2870 34" x 86" 35"x 87"
- 3070 38" x 86" 39"x 87"
- Frame Size _____ x _____

6. Panel Options

- Insulated Door Panel
- Rough Opening Buck
- Door Closure Reinforcement
- Panel Size _____ x _____
- _____

7. Lock Options

- Locking Knob (Round)
- Door Knob (no lock)
- Door Knob Bore
- Dead Bolt Bore
- S.S. Utility Latch
- _____

8.

" DOORS ARE NOT FIRE RATED"

Rough Opening Size _____ Wall Thickness _____

9.

COMPANY NAME _____

NAME _____ CITY _____

ADDRESS _____ STATE _____ ZIP _____

TELEPHONE _____ CELL.# _____ FAX _____

10.

Please Sign Customer Approval if all information is correct and return.

Customer Approval : _____ Date: _____

Note: Painting or use as Exterior Door will void Door Warranty.

For Office use Only:

5902 W. Custer Manitowoc, WI 54220 Phone 1-888-818-0118 Fax 920-684-4344

Phone 920-684-9650 www.epiplastics.com e-mail: info@epiplastics.com

