



**EXTRUTECH PLASTICS, INC.**

*"Custom Mistrader of Close Tolerance Profiles"*

**FOR QUOTE, FAX TO (920) 684-4344**

# Pre-Hung Corrosion Proof PVC Interior Doors

## 1. Door Location

- Door will be for Interior use only.

## 2. Door Swing

Circle your choice

**Note: Painting or use as Exterior Door will void Door Warranty.**

LEFT HAND	RIGHT HAND	LEFT HAND	RIGHT HAND
Quantity _____	Quantity _____	Quantity _____	Quantity _____
<b>SWING- OUT</b> (Door Swing)		<b>SWING- IN</b> (Door Swing)	

View Door Unit from outside room.

## 3. Frame Options

- 4 9/16" Jamb
- 6 9/16" Jamb
- PVC Sill       No Sill
- Colonial Casing       x2
- Brickmoulding       x2
- 3 1/2"x5/8 Foam Brd.       x2
- \_\_\_\_\_

## 4. Window Options

- 16 x 16 Window
- 20 x 24 Window
- \_\_\_\_\_ Window
- Insul Glass /  1/4" Plexi

## 5. Standard Door Size

*Size out to out      Rough opening*

- 2868 34" x 82"      35"x 83"
- 3068 38" x 82"      39"x 83"
- 2870 34" x 86"      35"x 87"
- 3070 38" x 86"      39"x 87"
- Frame Size \_\_\_\_\_ x \_\_\_\_\_

## 6. Panel Options

- Insulated Door Panel
- Rough Opening Buck
- Door Closer Reinforcement
- Door Closer - (Reversible)
- Door Latch Cover Plate
- Double Swing Door
- \_\_\_\_\_

## 7. Lock Options

- Locking.
- Knob(Round)       Lever
- NON Locking**
- Knob(Round)       Lever
- Door Knob Bore
- Dead Bolt Bore
- Lever Bore**
- Push / Pull Plates
- \_\_\_\_\_

## 8. " DOORS ARE NOT FIRE RATED"

Rough Opening Size \_\_\_\_\_ Wall Thickness \_\_\_\_\_

9. COMPANY NAME \_\_\_\_\_ DATE: \_\_\_\_\_  
 NAME \_\_\_\_\_ CITY \_\_\_\_\_  
 ADDRESS \_\_\_\_\_ STATE \_\_\_\_\_ ZIP \_\_\_\_\_  
 TELEPHONE \_\_\_\_\_ CELL.# \_\_\_\_\_ FAX \_\_\_\_\_

## 10. Please Sign Customer Approval if all information is correct and return.

Customer Approval : \_\_\_\_\_ Date: \_\_\_\_\_

**Note: Painting or use as Exterior Door will void Door Warranty.**

For Office use Only:

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

